

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number  
**WO 2005/085062 A1**

(51) International Patent Classification<sup>7</sup>: **B63C 9/00**,  
B65D 25/42, F16K 15/20, 41/08

(21) International Application Number:  
PCT/GB2005/000899

(22) International Filing Date: 7 March 2005 (07.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0405008.4 5 March 2004 (05.03.2004) GB

(71) Applicant (for all designated States except US): **MAN-  
GAR INTERNATIONAL LIMITED** [GB/GB];  
Presteigne Industrial Estate, Presteigne, Powys LD8  
2UF (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **FLETCHER,**

**Richard, Edmond** [GB/GB]; The Fold, Bircher, Leomin-  
ster, Herefordshire HR6 0AX (GB).


(74) Agents: **CHURCH, Simon** et al.; Wilson Gunn Skerrett,  
Charles House, 148/9 Great Charles Street, Birmingham  
B3 3HT (GB).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: FLUID FLOW CONNECTOR



(57) Abstract: Fitting for attachment to a mem-  
brane of an inflatable device comprises a mounting  
adapter (1) to be secured to said membrane. A re-  
siliently deformable part (5c) associated with said  
mounting adapter is arranged to embrace and hold  
an initially separate insert (2). The resiliently de-  
formable part (5c) is arranged such that when the  
mounting adapter is secured to the membrane and  
exposed to a force exerted by fluid at one of two  
sides of the membrane, the resiliently deformable  
part is urged into applying engagement with the  
insert (2). A variety of different inserts (2) hav-  
ing different valve arrangements can be held by the  
mounting adapter.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,  
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*